

Technical Information Ver-Omatic



The Ver-Omatic Treibgas/Verd. 275 pre-fill spray paint is prefilled with propellant and specific additives and then filled by filling device with the desired coat. Innovative spray and valve technology guarantee the fine broad jet atomisation, a high application rate and constant pressure for best workmanship and professional-quality end results. The Ver-Omatic Treibgas/Verd. 275 is a pre-filled can with propellant gases and solvent that can be filled with solvent-based basecoats.

Quality and properties Physical and chemical data

- A spray can pre-filled with propellant and solvents. The paint is transferred via a filling device into the can to produce a ready-to-use end product (dealers liability)
- Simple, time-saving application
- Excellent atomization
- Light blending

Ideal for spot or refinishing parts.

- **Colour:** depending on filling
- **Smell:** solvent
- **Efficiency:**
Depending on consistence and color of the ground.
- **Substrate:**
depending on filling
- **Drying time (at 20°C, 50% relative air humidity):**
the drying time depends on surrounding temperature, air humidity, thickness of the applied coat and the filled type of paint (refer to information of the paint manufacturer)
- **Storage stability:**
Empty cans: 5 years
Filled cans: depending on type of paint from several hours up to 6 months (information from specialist dealer): If appropriate storage provided (=10°-25°C, relative air humidity max. 60%)
- **Size:** aerosol cans, maximum nominal volume 400 ml, filling quantity 100 ml
- **VOC-value:** 218g

Disposal and labelling

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Using instructions

The most DUPLI-COLOR spray paints have a so-called no-spray ring or a tamper-proof cap. This is to avoid unauthorized use. Please see the corresponding advises on the cap or on the label.

Before use, carefully read and observe the warning texts on the label!

Application

Before use, carefully read and observe the warning texts on the label!

- Clean the surface to be painted thoroughly with silicone cleaner, then sand.
- Larger bare surfaces must be pre-primed with the appropriate primer.
- The area must be dry and free of dust and grease.
- Shake can vigorously for 2 minutes.
- Carry out spray test.
- Compatibility testing is necessary.
- For professional use only.

***Pay attention to manufacturer's instruction**

Tips for spray painting

Protect the object and the surrounding area from spray mist.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Order informations

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of July 12, 2018

This release replaces all eventually earlier issued versions.

Print date: 15.08.2026

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com