

## Technical Information Spraygun Cleaner for solvent- and water-based paints



ColorMatic spray gun cleaner efficiently, quickly and gently cleans spray guns of all dirt from solvent- and water-based paints. Because it is easy to use, ColorMatic spray gun cleaner saves a great deal of time and represents a portable, cost-effective alternative to a spray gun cleaning machine. It contains specific solvents, acetone and additives.

### Quality and properties

- Cleans spray gun gently, thoroughly, quickly from all impurities from solvent-based paints
- Extremely time saving
- Cost-effective alternative to spray gun cleaning machine
- Contains specific solvents, acetone and additives

### Physical and chemical data

- **Basis of binder:** solvent
- **Colour:** transparent
- **Smell:** solvent
- **Storage stability:**  
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
Aerosol cans, maximum nominal volume 400 ml
- **VOC-value:** 267g

### Environment and labelling

**Environmentally compatible:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

*Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.*

**Labelling:** All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

### Using instructions

**Before use, carefully read and observe the warning texts on the label!**

- Give can a quick shake
- Carry out spray test
- Disassemble spray gun immediately after painting and thoroughly spray to wash away all paint residues
- Wipe with a clean, dry non-woven / paper towel
- Leave cleaned parts to dry thoroughly



1-2

### Tips for spray painting

Protect the object and the surrounding area from spray mist. When painting small areas it is recommended that a piece of card is used as a mask, with a hole cut in it slightly larger than the area to be sprayed. The mask should be held 1 to 2 cm from the surface. With this method, the mainly part of the spray mist is brought under control. It recommends to mask parts not to be lacquered, to protect the surrounding against the spray mist.

The aerosol can should have room temperature.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

### Order information

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of July 26, 2010

This release replaces all eventually earlier issued versions

Print date: 27.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)