

Technical Information Eventmarker



DUPLI-COLOR Eventmarker is a white marker marking spray, ideal for markings that should remain visible only for a short time (e.g. for sporting events, fairs, identification of accident sites). Thanks to the special chalk base, the marking holds for just a few days to weeks and fades quickly during extended periods of rain or in high-traffic areas. Due to the contents that are **non-hazardous to plants** also ideally suited for garden and landscaping as well as for sports and golf courses.

Patented one-hand safety cap for improved functionality and increased safety. Guaranteed marking without painted fingers. Now new with Easy-Touch-release.

Particularly environmentally friendly thanks to use of selected ingredients.

The Eventmarker can be used in the following accessories **Accessories:**

- Speedmarker long
- Speedmarker short
- Speedmarker 2-wheel

Quality and properties

- For temporary markings
- For indoor and outdoor applications
- Easily removed with water
- Innovative one-hand safety cap with lockable spray trigger prevents unintentional spraying
- Special tilt valve for accurate wall and floor markings
- Outstanding adhesion to wet surfaces as well
- High coverage quality ensures high yield
- Simple to use also with gloves
- Clean, drip-free marking
- Cap acceptable for special applications (for use in accessories)
- Environmentally friendly and non-hazardous to health
- Can be 100% emptied by spraying thanks to self-cleaning system, no venting therefore required

Physical and chemical data

- **Basis:** Chalk
- **Colour:** white
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity max. 60%).
- **Efficiency:**
Depending on condition and colour of the ground, 500 ml are sufficient for up to 140 m
- **Drying (at 20°C, 50% relative air humidity):**
Dust-dry: after approx. 10 minutes
Dry to touch: after approx. 30 minutes
Cured: after approx. 24 hours
Can be overworked: after approx. 24 hours
The drying time depends of temperature of surroundings, air humidity and thickness of the applied layer.
- **Contents:** aerosol cans with max. nominal volume of 500 ml

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

The most DUPLI-COLOR spray paints have a so-called no-spray ring or a tamper-proof cap. This is to avoid unauthorized use. Please see the corresponding advises on the cap or on the label.

Before use, carefully read and observe the warning texts on the label!

Application

- Shake can for approx. 3 minutes.
- Test spray at an invisible spot.
- Spray distance approx. 25 cm.
- Apply the desired marking.
- In case of use in the Speedliner² marking trolley, attend to the corresponding manual.

Tips for spray painting

Protect the object and the surrounding area from spray mist. When painting small areas it is recommended that a piece of card is used as a mask, with a hole cut in it slightly larger than the area to be sprayed. The mask should be held 1 to 2 cm from the surface. With this method, the mainly part of the spray mist is brought under control. It recommends to mask parts not to be lacquered, to protect the surrounding against the spray mist.

The aerosol can should have room temperature.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of September 5, 2010

This release replaces all eventually earlier issued versions.

Print date: 02.05.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com