

Technical information Finish Control Spray



ColorMatic finish control spray provides optimum results after polishing the clear coat and topcoat, where appropriate. The micro foam removes oily and waxy polish residue and makes remaining sanding marks visible.

Application:

Ideal for spot repairs and refinishing parts.

Quality and properties

- Removes oily and waxy polish residue
- Makes remaining marks visible
- Easy and fast application
- Mild, non-aggressive cleaning agent
- Very time saving
- Used after polishing sanded coated surface (dust inclusions, paint defects, frosted edges)

Physical and chemical data

- **Basis of binder:** Acrylic
- **Colour:** transparent, foaming
- **Smell:** solvent
- **Efficiency:**
Depending on consistence and colour of the ground:
400 ml are sufficient for approx. 2,0 m²
- **Substrate:**
Sanded and polished clearcoat or topcoat surface
- **Drying-time (at 20°C, 50% relative air humidity):**
Dust-dry: after approx. 10 minutes
Dry to touch: after approx. 30 minutes
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature resistance:** to 80°C
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**
Aerosol cans, maximum nominal volume 400 ml
- **VOC-value:** 89,7g

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Using instructions

Before use, carefully read and observe the warning texts on the label!

- Apply a thin layer on the polished surface
- Wipe dry with a clean, soft cloth (do not leave to dry)
- If sanding marks or holograms are visible, polishing is required
- Repeat above procedure until results are perfect
- **For professional use only**

Hints concerning application

ColorMatic finish control spray exposes even holograms that have developed during polishing work. Just use after polishing as instructed.



Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of July 26, 2010

This release replaces all eventually earlier issued versions.

Print date: 28.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com