

Technical Information Carpet Spray Paint



ColorMatic mattenspray is een gebruiksvriendelijke spray voor het oprispen en kleuren van automatten en tapijten van textiel voor personenauto's en bedrijfswagens. Eenvoudig en snel lamineren van vlekken en kleurvervaging. Biedt een hoge dekking en goede hechting. Toepasbaar op textielmatten en door specifieke additieven ook op rubber automatten.

Toepassing:

Voor het oprispen van de kleur en het kleuren van textielmatten en tapijten in auto's en bedrijfsvoertuigen.

Quality and properties

- High-quality acrylic coat
- Simple application
- User-friendly restoration of wears on textile car mats and carpets
- Laminates stains and wears
- Applicable on textile and rubber car mats
- Tip: After every spray pass we recommend to rework the still wet lacquer film with a brush so the carpet fibres are throughout moistened with color and will not stick together.

Physical and chemical data

- **Basis of binder:** Acrylic
- **Colour:** Black and anthracite
- **Smell:** solvent
- **Efficiency:**
Depending on consistence and colour of the ground:
400 ml are sufficient for approx. 1,25 - 1,75 m²
- **Drying time (at 20°C, 50% relative air humidity):**
Dust-dry: after approx. 5 min
Dry to touch: after 30 min
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature resistance:** to 90°C
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**
Aerosol cans, maximum nominal volume 400 ml
- **VOC-value:** 238 g

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Using instructions

Before use, carefully read and observe the warning texts on the label!


- Surfaces should be free of dust
- Shake can well for 2 minutes
- Carry out spray test
- Spray several thin coats at intervals of 5 minute
- Tip: After every spray pass we recommend to rework the still wet lacquer film with a brush so the carpet fibres are throughout moistened with color and will not stick together.
- **For professional use only**
- **Wear an appropriate respirator (recommended type A2/P3)**




2 min




2-3




5 min



20°C=60 min



15-20 cm



approx. 1m²

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of February 1, 2016

This release replaces all eventually earlier issued versions

Print date: 28.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com