

Technical Information Structure Spray



DUPLI-COLOR Structure Spray creates an individual surface structure, similar to a rough plaster. It is an exclusive, water-based polyurethane dispersion, which is suitable to repair and adapt a textured plastering. It can be used on misc. surfaces, such as concrete, gypsum plasterboard, sheetrock, wood etc. Can be overcoated with all dispersion paints.

Quality and properties

- bright white colour
- easy to apply
- good coverage
- fast-drying
- excellent adhesion
- repaintable with common wall paints
- for inside use

Physical and chemical data

- **Basis of the binder:** polyurethane dispersion
- **Colour:** white
- **Efficiency:**
500 ml are sufficient for approx. 1 m²
- **Drying time (at 21°C, 45 % relative air humidity):**
repaintable after 2 hours
The drying time depends on surrounding temperature, air humidity and absorptivity of the ground.
- **Storage stability:**
2 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
Do not store below 5°C
- **Size:** 500 ml aerosol can

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Using instructions

Before use, carefully read and observe the warning texts on the label!

- If there are water stains, smoke or grime spots, we recommend to use first DUPLI-COLOR Blocking Primer.
- The surface has to be dry, clean, free from fat and wax as well as sanded.
- Shake can vigorously for 3 minutes and test spray on a carton or a wooden plate.
- Spray from a distance of approx. 25-30 cm.
- Spray in circular, permanent movements.
- Let dry.
- In order to achieve a thicker structure, spray again and let the spot dry.
- Turn can after use upside-down and spray several seconds, in order to clean the valve.

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of April 13, 2018
This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com