

Technical Information Aqua Floor Paint



DUPLI-COLOR Aqua Floor Paint is the universal coating for all kinds of flooring. Paint and primer on one product. Ideal suitable for all highly demanded floors in interior as well as in protected exterior premises.

Possible grounds: mineral grounds such as concrete or chalk bonded areas (e.g. screed, plaster, concrete, masonry, even natural stone). Not suitable for garage floors!

Quality and properties

- resistant to wiping and yellowing
- for interior and protected outside premises
- ease of working
- quick-drying
- eco-friendly, poor bad odour
- water-based

Physical and chemical data

- **Basis of the binder:** acrylatdispersion, water-based
- **Colour:** misc.
- **Smell:** neutral
- **Efficiency:**
Depending on thickness of layer
750 ml are sufficient for approx. 6 m²
2.5 L are sufficient for approx. 20 m²
5 L are sufficient for approx. 40 m²
- **Drying time (at 20°C, 65% relative air humidity):**
Surface-dry after approx. 2 hours
Coatable after 12 hours
The drying time depends on surrounding temperature, air humidity and absorptivity of the ground.
- **Cleaning of tools:** immediately after use with water
- **Storage stability:**
5 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%) in the unopened original container.
Do not store below 5°C
- **Size:** metal tins 750 ml, 2.5 L and 5 L

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Using instructions

Before use, carefully read and observe the warning texts on the label!

Preparation of the ground:

- The surface has to be bearing, dry, clean and free from fat.
- Remove cement slurry, limescale, oxid film or releasing agents without residues; rewash thoroughly.
- New concrete areas have to dry at least 4 - 6 weeks.

Painting:

- Before application, always carefully stir up the paint
- Temperature of the object and surrounding temperature should be at least +7°C
- Brush or roll
- Priming coat with this Aqua Floor Paint, diluted with approx. 10 % water (10 ml to 100 ml paint)
- Intermediate coat with this Aqua Floor Paint, diluted with approx. 5 % water (5 ml to 100 ml paint)
- Final coat with this Aqua Floor Paint, undiluted
- Between the coats, slightly sand and clean the ground.

Coat to renovate:

- Sand good preserved old coatings thoroughly, clean them and recoat as described under "Final coat". Remove without residues flaking and not bearing old coats (remove with a paint stripper, sand down).

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of March 28, 2018

This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com