

## Technical Information Fence Lasure



DUPLI-COLOR Fence lasure is a weather-proof wood paint for exterior premises. Without biocide. For all exterior wood constructions, such as wood fences, garden doors, palisades, pergola, garden houses, barns, piles etc.

### Quality and properties

- Free from biocides
- Neutral smell
- Water thinnable
- For exterior

### Physical and chemical data

- **Basis of the binder:** Synthetic dispersion
- **Colour:** brown
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530): not relevant
- **Efficiency:**  
5 l are sufficient für approx. 50 m² depending on the ground
- **Drying time (at 20°C, 65% relative air humidity):**  
Surface-dry after approx. 2 hours  
Coatable after 4 hours  
The drying time depends on surrounding temperature, air humidity and absorptivity of the wooden ground.
- **Storage stability:**  
5 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%) in the unopened original container.
- Do not store below 5°C
- **Size:** plastic container with 5 L

### Environment and labelling

**Environmentally sound:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling:** All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

### Using instructions

**Before use, carefully read and observe the warning texts on the label!**

#### Preparation of the ground:

In order to ensure adhesion and to achieve best image of painting, prepare the surface as follows:

- The areas to be painted have to be clean, dry, dust- and fat-free, firm and bearing.
- Old paintings: when intact clean and sand, otherwise with a paint remover.
- Remove without residues flaking, not bearing coatings.
- Prime: to prevent fungal attacks oder if parts have direct contact to the ground earth, use DUPLI-COLOR Wood impregnation.
- The minimum temperature for material and surroundings is 8°C

#### Glazing:

- Stirr well before use.
- Brush (with a glazing brush)
- Optimal result at 2 paintings (undiluted)
- The colour of the wood influences the colour of the lasure, we recommend a test.
- After use immediately clean the tools with warm water and soap.

#### Tips for an optimal result:

- Sand, clean and brush the wood always in direction of the fibers.
- In order to achieve an even, natural coat of paint, we recommend to apply several thin coast instead of one thick coat.
- Consider a drying time of 4 hours between the coats.

### Order information

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond

our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of March 13, 2018

This release replaces all eventually earlier issued versions.

Print date: 02.05.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)