

Technical Information Marker for Construction and Forestry (sprayhead for writing)



DUPLI-COLOR Marking Spray for Construction and Forestry for temporary markings, especially on tree trunks and timber. Also suitable for markings on streets and buildings.

The special sprayhead with capillary tube allows to spray plane, but also writings.

Available colours: fluorescent: blue, yellow, green, orange, red, non-fluo: white and black

Optional accessory:

- Metal spray handle

Quality and properties

- Special spray nozzle for plane applications and also for targeted writing
- Excellent adhesion even on humid surfaces
- Markings shine bright for 6 - 9 months
- Excellently covering quality grants high efficiency
- Intensive luminance of the fluorescent shades
- Environmentally sound and not hazardous to health
- Safe during frost up to -10°
- Self-cleaning valve

Physical and chemical data

- **Basis:** acrylic
- **Colour:** diverse
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity max. 60%).
- **Efficiency:**
Depending on condition and colour of the ground,
500 ml are sufficient for up to 140 m
- **Drying (at 20°C, 50% relative air humidity):**
Dust-dry: after approx. 10 minutes
Dry to touch: after approx. 30 minutes
Cured: after approx. 24 hours
Can be overworked: after approx. 24 hours
The drying time depends of temperature of surroundings, air humidity and thickness of the applied layer.
- **Contents:** aerosol cans with max. nominal volume of 500 ml

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Application

- Shake can for approx. 3 minutes.
- Test spray at an invisible spot.
- Spray distance approx. 25 cm.
- Apply the desired marking.

Tips for spray painting

Protect the object and the surrounding area from spray mist. When painting small areas it is recommended that a piece of card is used as a mask, with a hole cut in it slightly larger than the area to be sprayed. The mask should be held 1 to 2 cm from the surface. With this method, the mainly part of the spray mist is brought under control. It recommends to mask parts not to be lacquered, to protect the surrounding against the spray mist.

The aerosol can should have room temperature.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of September 5, 2010

This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com