

## Technical Information Linemarker



DUPLI-COLOR Linemarker for longlasting applications. Very durable quality.

Suitable for the marking of lines, parking lots, in industrial plants as well as for private purposes. With upside-down valve.

Available colour hues: blue, yellow, red and white.

The line marker can be used in the following accessories:

- Speedliner<sup>®</sup>
- Speedmarker long
- Speedmarker short
- Speedmarker 2-wheel

## Quality and properties

- High coverage, quick drying quality
- Special valve for floor applications ensures sharp edges
- Specially for use in Speedliner<sup>®</sup>
- For permanent markings
- Highly resistant to abrasion
- High weather resistance

## Physical and chemical data

- **Basis:** acrylic
- **Colours:** diverse
- **Storage stability:**  
10 years if appropriate storage provided (=10°-25°C, relative air humidity max. 60%).
- **Efficiency:**  
Depending on condition and colour of the ground,  
600 ml are sufficient for approx. 60 m of 10 cm wide lines
- **Drying (at 20°C, 50% relative air humidity):**  
Dust-dry: after approx. 10 minutes  
Dry to touch: after approx. 30 minutes  
Cured: after approx. 24 hours  
Can be overworked: after approx. 24 hours  
The drying time depends of temperature of surroundings, air humidity and thickness of the applied layer.
- **Contents:** aerosol cans with max. nominal volume of 600 ml

## Environment and labelling

**Environmentally sound:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling:** All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

## Application

- Shake can for approx. 3 minutes.
- After you hear the sound of the balls inside the can, vigorously shake the can for one more minute.
- Test spray at an invisible spot.
- Spray distance approx. 25 cm.
- Apply the desired marking.
- In case of use in the Speedliner<sup>®</sup> marking trolley, attend to the corresponding [manual](#).

## Tips for spray painting

Protect the object and the surrounding area from spray mist. When painting small areas it is recommended that a piece of card is used as a mask, with a hole cut in it slightly larger than the area to be sprayed. The mask should be held 1 to 2 cm from the surface. With this method, the mainly part of the spray mist is brought under control. It recommends to mask parts not to be lacquered, to protect the surrounding against the spray mist.

The aerosol can should have room temperature.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

## Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

Stand: 5. September 2010

Mit dieser Version werden alle evtl. früher erschienenen Versionen ungültig.

Print date: 30.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wol Vega | NL | [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)