

Technical Information RUST STOP Hammerfinish



Active rust prevention by effective thick-film paint system in satin matt quality.

In the liquid-corrosion-inhibitor technology (LCI), a special system of integrated additives has been developed. These completely enclose the structures of the surface you want to paint and thus form a chemical connection. By this, the continuing oxidation stops and achieves a durable rust-protection. This rust protecting paint system combines 4 properties in 1 product:

1. Effective **primer** for perfect adhesion
2. Active **rust protection** by LCI technology
3. Highly covering **spray paint**
4. **Sealant** protecting from environmental influences

Adheres on nearly all surfaces, such as iron, blank and zinc-plated steel plates, copper, brass, aluminium (e.g. garden fences, gates, banisters, gardening tools etc.). Even applicable on tightly adhering rust and old paintings. Also applicable on wood, stone, GRP or glass.

Quality and properties

- High-grade nitro-combi quality
- Distinct hammerfinish covers small unevennesses in the surface
- Saves precious working time: no derusting and repeated lacquering
- Reduced cost, as no anti-rust products necessary
- Longlasting corrosion protection
- Quick-drying
- Very good flow
- High coverage and filling power
- High elasticity
- Shock-proof and impact resistant after drying
- Excellent adherence
- UV-resistant, non-yellowing
- Weather-resistant, waterproof
- Successfully tested in salt spray test over 500 hours
- Variable broad jet atomisation for horizontal or vertical spraying and a wide, proper spray pattern

Physikalische und chemische Daten

- **Basis of the binder:** Nitro-combi
- **Colour:** specific
- **Smell:** solvent
- **Degree of gloss:** measuring angle 60° after DIN 67530 not measurable due to structured surface
- **Efficiency:**
Depending on condition and colour of the ground, 400 ml are sufficient for approx. 0.8 - 1.5 m²
- **Drying (at 20°C, 50% relative air humidity):**
Dust-dry: after approx. 5 minutes
Dry to touch: after approx. 20 minutes
Cured/coatable: after approx. 60 minutes
The drying time depends of temperature of surroundings, air humidity and thickness of the applied layer.
- **Temperature-resistance:** up to 80°C
- **Disposal:** Put only empty cans into the recycling bin. Bring cans with remainders of paint to the special refuse disposal.
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity max. 60%).
- **Contents:** aerosol cans with max. nominal volume of 400 ml

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Using instructions

The most DUPLI-COLOR spray paints have a so-called no-spray ring or a tamper-proof cap. This is to avoid unauthorized use. Please see the corresponding advises on the cap or on the label.

Before use, carefully read and observe the warning texts on the label!

Anwendung

- Lose Bestandteile auf trockenen, rostigen Metallflächen mit einer Drahtbürste entfernen.
- Auf glatten, blanken Metalloberflächen ist ein leichtes Anschleifen empfehlenswert.
- Der Untergrund muss sauber, trocken und fettfrei sein.
- Zur Verbesserung der Haftung empfehlen wir, Plastikteile mit DUPLI-COLOR Plastic Primer vorzubehandeln.
- Dose 3 Min. schütteln.
- An unauffälliger Stelle Probesprühen und auf Lackverträglichkeit prüfen.
- Nicht zu lackierende Flächen abkleben.
- Mehrere dünne Schichten sprühen.
- Sprühentfernung ca. 25 cm.
- **Nicht auf Kunstharzlacke sprühen!**

Tips for spray painting

Protect the object and the surrounding area from spray mist. When painting small areas it is recommended that a piece of card is used as a mask, with a hole cut in it slightly larger than the area to be sprayed. The mask should be held 1 to 2 cm from the surface. With this method, the mainly part of the spray mist is brought under control. It recommends to mask parts not to be lacquered, to protect the surrounding against the spray mist.

The aerosol can should have room temperature.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of May 5, 2010

This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com