

## Technical Information Rallye Lacquer



For contrast and partial lacquering, for example rally stripes at the car and many other purposes. Also applicable on rims and car body.

To embellish rims, we recommend MoTip Rallye Wheel Paint in silver or gold.

### Quality and properties

- High-grade nitro-combi quality
- Very good coverage
- Excellent adhesion
- Good flow, smooth surface
- Quick-drying
- Suitable for indoors and outdoors applications
- Weather-resistant, light-proof, UV-resistant
- Scratch-, shock- and impact-resistant
- High surface hardness and good elasticity
- Polishable, dirt-resistant surface

### Physical and chemical data

- **Basis of the binder:** acryl resin
- **Colour:** black or white, glossy, satin mat or matt
- **Smell:** solvent
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530):  
glossy: 80-85 gloss units  
satin matt: 30-40 gloss units  
matt: 10-20 gloss units
- **Efficiency:**  
Depending on consistence and color of the ground:  
12ml for several applications  
150 ml are sufficient for approx. 0.5 m²  
500 ml are sufficient for approx. 1.5 - 2.0 m²
- **Drying time (at 20°C, 50% relative air humidity):**  
12 ml:  
Dust-dry: after approx. 15 minutes  
Dry to touch: after approx. 60 minutes  
150 ml / 500 ml:  
Dust-dry: after approx. 5-10 minutes  
Tack-free: after approx. 10-20 minutes  
Coatable: after approx. 2 hours  
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature-resistant:** up to 110°C
- **Storage stability:**  
touch-up pencils: 5 years, aerosols: 10 years, if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
touch-up pencils 12 ml,  
aerosol cans, maximum nominal volume 150 ml resp. 500 ml

### Environment and labelling

**Environmentally sound:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling:** All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

### Instruction manual

**Before use, carefully read and observe the warning texts on the label!**

#### Preparation of the ground:

- Clean underground from dirt, fat and rust.
- Fill and sand uneven surfaces.
- If no filling with putty is necessary, apply a primer, e.g. MoTip Rallye Primer.
- Otherwise apply MoTip Filler on the fine-sanded filled surfaces. Before that, generously mask off the repair spot.
- If bigger areas have to be repaired, we recommend to mask off edges of the car body.

#### Lacquering:

- The surface has to be clean, dry and free from fat.
- Mask off areas not to be painted.
- Before use, shake the can vigorously for 3 minutes.
- Test spray to check colour-matching.
- The spray distance should be approx. 20-30 cm.
- Spray several thin cross-coats in 3 - 5 minute intervals.
- Do not spray over synthetic paints!

### Tips for spray painting

Protect the object and the surrounding area from spray mist. When painting small areas it is recommended that a piece of card is used as a mask, with a hole cut in it slightly larger than the area to be sprayed. The mask should be held 1 to 2 cm from the surface. With this method, the mainly part of the spray mist is brought under control. It recommends to mask parts not to be lacquered, to protect the surrounding against the spray mist.

The aerosol can should have room temperature.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

#### **Disclaimer of liability**

---

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: February 1, 2012

This release replaces all eventually earlier issued versions.

Print date: 30.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)