

## Technical Information Industrial Chain Grease



Spray to lubricate chain-driven transmissions, which are liable to heavy load. Industrial chain grease can be processed like oil, with the properties of grease. Industrial chain grease has outstanding mechanical and thermal stability and prevents wear and sticking. Industrial chain grease is resistant to weather influences and weak acids and bases, is water-repellent and pH-neutral. MoTip Industrial Chain Grease is resistant to temperatures of - 50°C up to + 200°C.

### For use on:

For all types of chain drives such as bicycles, motorbikes, mopeds, farm machines, in ships, car repair workshops or maintenance workshops.

## Quality and properties

- To be processed like oil, with the properties of grease
- Outstanding mechanical and thermal stability
- Good adhesion
- Dilatant
- Prevents wear and sticking
- Resistant to weather influences
- Resistant to weak acids and bases
- Water-repellent
- Directed jetspray

## Physical and chemical data

- **Basis:** mineral oil
- **VOC-content:** approximately 39% w/w
- **Colour:** transparent yellow
- **Smell:** characteristic
- **Relative density at 20°C:** 0.844 g/ml
- **Yield:** 2.0 g/sec.
- **Vapour pressure at 20°C:** 3 - 4 bar
- **4 Ball EP-test (AS TM D 2596):** 3430 N
- **Temperature resistance:** -50°C to +200°C
- **pH-value:** neutral
- **Storage stability:**  
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
aerosol can, maximum nominal volume 500 ml

## Environment and labelling

**Environmentally sound:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling:** All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

## Instruction manuel

**Before use, carefully read and observe the warning texts on the label!**

### Application:

- Bring can to room temperature.
- Operating temperature 5° to 30°C.
- Shake for 2 minutes before use.
- We recommend cleaning the chain with MoTip degreaser.
- Spray Chain Grease evenly onto chain.
- Has a foamy appearance in the beginning stages when the product can penetrate deep into the treated chain.
- Works like oil, but has the properties of grease.
- Optimum lubrication occurs once the solvent has evaporated (approx. 5 minutes).

## Tips for spray painting

Protect the object and the surrounding area from spray mist.  
Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

## Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: October 1, 2014

This release replaces all eventually earlier issued versions.

Print date: 30.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)