

Technical Information Marking Spray



MoTip Marking Spray offers excellent coverage and intense brightness for long-lasting and resilient markings in car parks, storage areas and fork lift truck routes. For use on stone, concrete, asphalt and metal. The 360° valve facilitates perfect all-round marking in every direction.

It is available in white, yellow, red and grey.

Use marking cart for exact mark linings.

Quality and properties

- Excellent coverage
- Fast drying time
- Scratchproof
- Resistant to petrol, chemicals and weather conditions

Physical and chemical data

- **Basis of the binder:** acryl resin
- **Colour:** white, yellow, red, grey
- **Efficiency:**
Depending on consistence and color of the ground:
600 ml are sufficient for approx. 60 m
- **Drying time (at 20°C, 50% relative air humidity):**
Cured: after 16 hours
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**
aerosol cans, maximum nominal volume 600 ml

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EEG in the actually valid version.

Instruction manual

Before use, carefully read and observe the warning texts on the label!

Application:

- The surface should be clean, dry and free of grease.
- Bring the can to room temperature.
- Operating temperature 15 to 25°C.
- Shake for 2 minutes before use.
- Test on inconspicuous area.
- Apply required width of spray.
- For optimum results, we recommend a speed of 1 metre per 4 to 5 seconds.
- After use, hold upright and spray empty to clean the valve.

Tips for spray painting

Protect the object and the surrounding area from spray mist. When painting small areas it is recommended that a piece of card is used as a mask, with a hole cut in it slightly larger than the area to be sprayed. The mask should be held 1 to 2 cm from the surface. With this method, the mainly part of the spray mist is brought under control. It recommends to mask parts not to be lacquered, to protect the surrounding against the spray mist.

The aerosol can should have room temperature.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: May 10, 2010

This release replaces all eventually earlier issued versions.

Print date: 01.05.2024

European Aerosols | Wolframweg 2 | 8471 XC Wolveg | NL | info-nl@european-aerosols.com

