

## Technical Information Shock Oil



Spray to clean and protect stainless steel parts. In view of the unique formula, after cleaning a thin protecting film is formed, which effectively prevents renewed adhesion of dirt. Stainless steel cleaner has good corrosion prevention and restores and intensifies the gloss. MoTip Stainless Steel Cleaner is user-friendly, gives lasting protection and is non polishing.

### Quality and properties

- Excellent cleansing properties
- Good corrosion prevention
- Restores and intensifies the gloss
- 360° valve
- Lasting protection
- Non polishing
- Misty spray pattern
- User-friendly

### Physical and chemical data

- **Basis:** Combination of mineral oil and specific additives
- **VOC-content:** approximately 80% w/w
- **Colour:** transparent
- **Smell:** Lemon
- **Relative density at 20°C:** 0.74 g/ml
- **Yield:** 1.18 g/sec.
- **Vapour pressure at 20°C:** 3 - 4 bar
- **Refractive Index Oil at 20°C:** 1,46 (ASTM D1218)
- **Viscosity oil at 20°C:** 13 (mPa.s)
- **Storage stability:**  
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
aerosol can, maximum nominal volume 500 ml

### Environment and labelling

**Environmentally sound:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling:** All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

### Instruction manuel

**Before use, carefully read and observe the warning texts on the label!**

#### Application:

- Bring can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can before use.
- To prevent scratches, remove loose dirt with a soft brush.
- Apply stainless steel cleaner in a thin, equal layer and allow to effect. Remove the dirt with a clean cloth. Polish to gloss with a dry, clean cloth.

### Tips for spray painting

Protect the object and the surrounding area from spray mist.  
Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: October 01, 2014

This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)