

### Qualität und Eigenschaften

- professional repair glue for automotive parts, plastic parts, or similar
- Epoxy-Quality
- Free of isocyanate
- quick-setting
- user-friendly 2-component packaging
- resealable cartridges

#### Set includes:

- 30ml 2-component repair glue
- 1 plastic putty
- fibre mat

### Physical and chemical data

- **Colour:** green
- **Smell:** characteristic
- **Working time at 20°C:** 2-3 minutes
- **Set time at 20°C:** 5-7 minutes
- **Cure time at 20°C:** 45-60 minutes; sandable already after 15-20 minutes
- **Storage stability:**  
2 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
30ml

### Environment and labelling

**Environmentally sound:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling:** All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

### Using instructions

The most presto spray paints have a so-called no-spray ring or a tamper-proof cap. This is to avoid unauthorized use. Please see the corresponding advises on the cap or on the label.

**Before use, carefully read and observe the warning texts on the labels!**

#### Application

- Clean areas to be repaired, sand (P80-P180) and remove dust and fat from the surface.
- Remove cap and cut off cartridge tips at the perforation.
- Cut fibre mat to the desired size, put the sticky side evenly on the surface.
- Use enclosed plastic putty knife to mix the material well.
- Apply an even coat (approx. 2-3 mm)
- Eventually firmly fixate (clamp) the repair piece.
- The working time is 2-3 minutes.  
Cure time: 45-60 minutes.

### Tips for spray painting

Protect the object and the surrounding area from spray mist. When painting small areas it is recommended that a piece of card is used as a mask, with a hole cut in it slightly larger than the area to be sprayed. The mask should be held 1 to 2 cm from the surface. With this method, the mainly part of the spray mist is brought under control. It recommends to mask parts not to be lacquered, to protect the surrounding against the spray mist.

The aerosol can should have room temperature.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of August 18, 2012

This release replaces all eventually earlier issued versions.

Print date: 28.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)