

Technical Information Acrylic Scratch Remover



Acrylic and Plexiglas® objects, e.g. rear lights, windows of convertibles, caravans, windscreens and covers for instruments etc., scratch very easy and, thus, lose their appearance and, thus, their value

Using the presto Acrylic Scratch Remover, these scratches can be easily, quickly and reliably disposed of: New from old! Thus, an expensive repair, or even replacement, can often be prevented.

Quality and properties

- Reliably removes scratches from acrylic and Plexiglas® surfaces of the car, motorcycle, caravan, boat, furniture etc.
- Quick and easy application
- All-inclusive kit contains everything required for application
- Attains results in professional quality, also for deeper scratches

Physical and chemical data

Chemical base: Mixture of the substances listed in the safety data sheet

Consistency: firm Colour: white Odour: characteristic

Density: 1,294 g/cm² pH-value: not determinable Flashpoint: 270°C

Storage stability:
36 months in the closed original package if cool and dry storage provided (=5°-25°C, relative air humidity of max. 60%). Protect from direct sunlight, frost and humidity.

Size: PLASTIC POLISH 50g tube, 1 polishing cloth, 2 special

sand papers

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Using instructions

Before use, carefully read and observe the warning texts on the label!

Application

- 1. Clean the surface and apply a little paste.
- 2. Using a soft, clean cotton cloth or pad polish the scratched areas using heavy pressure for 2-3 minutes. Do not use on any printed, varnished or coated surfaces.
- 3. For deep scratches repeat application several times.
- 4. Remove residue with a cloth.
- 5. Very deep scratches should be treated beforehand with special abrasive paper (granularity: 1500) and a little water. Polish afterwards with presto Acrylic Scratch Remover.
- . Warning: Do not use on any printed, varnished or coated surfaces. Do not use on Polycarbonate (PC). To be on the safe side, first test the polish on an unexposed surface.

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: May 3, 2017

This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

Furnnean Aerosols I Wolfraamweg 2 I 8471 XC Wolvega I NI Tinfo-nl@euronean-aerosols.com

	amneg = o n + x o none;	 	