

## Technical Information Assembly Cleaner

---



presto assembly cleaner is a highly effective rapid cleaner for the maintenance, repair and installation of machinery, vehicles, precision mechanical and tools. It dissolves old and hardened oil and fat residues as well as remnants of brake fluid and silicone. The cleaner serves as pre and basic cleaning and degreases all sliding surfaces and parts prior to the application of special lubricants.

### Qualität und Eigenschaften

---

- High solvency power
- Leaves no residue
- Non-conductive
- Non-corrosive
- Removes tough oil and grease
- Powerful directed jet spray
- Can be sprayed from any angle due to a special 360 ° valve.
- Observe TRG 300

### Physical and chemical data

---

- **Basis:** Aliphaton
- **Colour:** transparent
- **Smell:** aliphatic
- **Density at 20°C:** 0,67 g/ml
- **Yield:** 3-4 g/sec.
- **Vapour pressure at 20°C:** 5,5 - 6,0 bar
- **Propellant:** carbon dioxide
- **Storage stability:**  
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
aerosol can, maximum nominal volume 500 ml

### Environment and labelling

---

**Environmentally sound:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling:** All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

### Using instructions

---

**Before use, carefully read and observe the warning texts on the label!**

#### Application :

- Make sure can is at room temperature.
- Application temperature 5 ° to 30 ° C.
- Cover painted and plastic parts.
- Shake can well before use.
- Spray the parts to be treated until the dirt disappears.

### Order informations

---

### Disclaimer of liability

---

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of December 17, 2009

This release replaces all eventually earlier issued versions.

Print date: 27.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)