

## Technical Information Aircondition Cleaner



presto Aircondition Cleaner cleans and freshens air in vehicle air conditioning and circulation systems.

The cleaner forms foam after being applied on the vaporiser and the heating ducts and releases a pleasant fragrance.

### Quality and properties

- Lasting protection for smells
- Subtle scent
- Effective cleaning foam
- TRG 300 compliant

### Physical and chemical data

- **Basis:** Tenside solution
- **Colour:** white
- **Smell:** Orange
- **Appearance:** white foam
- **Relative density at 20°C:** 0.967 g/ml
- **Coverage:** one can for cleaning of a air-conditioning system
- **pH-value:** 9.5 - 10.5
- **Storage stability:**  
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
aerosol can, maximum nominal volume 400 ml

### Environment and labelling

**Environmentally sound:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling:** All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

### Using instructions

**Before use, carefully read and observe the warning texts on the label!**

#### Application:

- The aerosol should have room temperature.
- Best processing temperature 5 to 30°C.
- Before use, shake the aerosol.
- Before treatment, switch off the engine and the electrical installations.
- Apply the foam to the evaporator of the air conditioning by means of the enclosed adapter.
- Insert the adapter about 30 centimetres into the air inlet of the air conditioning and completely empty the can.
- The location of the air inlet differs per brand, consult your dealer.
- After applying, do not switch on the engine or the electrical installations for at least half an hour.
- In this half hour the foam will break and leave the system through the condensed water outlet as a fluid.

### Tips for spray painting

Protect the object and the surrounding area from spray mist.  
Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of August 4, 2016  
This release replaces all eventually earlier issued versions.

Print date: 30.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)

