

## **Technical Information Silicone Remover**



presto Silicone Remover is essential for professional paintwork results because it thoroughly removes dirt, grease, oil, silicone, wax, tar, adhesive residues etc. presto silicone remover saves a great deal of time because it is quick and easy to use and universally applicable. It enhances adhesion for subsequent coatings.

**Applications:** 

Ideal for spot repairs and refinishing parts, as well as all work that requires a professional clean.

## Quality and properties

- Simple application
- Thorough removal of silicone, grease, oil, wax, dirt, tar, adhesive residues etc
- Mild, non-aggressive solvent
  Improves adhesion of subsequent coatings
- Extremely time saving

#### Physical and chemical data

- Colour: transparent
- Smell: solvent
- Substrate:
- primed and filled areas
- metal, glass old paints and original paints from supplier painted and unpainted surfaces Storage stability:
- 10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- Size: aerosol can, maximum nominal volume 500 ml

### **Environment and labelling**

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

#### Using instructions

# Before use, carefully read and observe the warning texts on the label!

## Application:

- Shake briefly.
- Spray at a distance of 20 25 cm.
- Spray evenly the surface with silicone remover and wipe off with a clean, dry paper towel.
- If heavily solled, repeat the procedure.
- Let evaporate well the cleaned surfaces.

#### Order informations

#### **Disclaimer of liability**

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of octobre 4, 2016 This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com