

## Technical Information Vaseline Spray



presto Vaseline Spray is a reliable lubrication that also protects metals such as aluminium, copper, brass, chrome, steel etc. from acids, lyres and salt.

### For use on:

Antennae, plug-in connections and bolted connections and locks

## Quality and properties

- Prevents wear and clamping of treated parts
- Medicinal qualities
- Non-poisonous on contact with food
- Water repellent
- Non-conducting
- Excellent lubrication
- Excellent mechanical stability
- Resistant to the effects of weather
- Saltwater, weak acid and lyre proof
- Excellent adhesion
- Good corrosion protection
- Acid free
- Misty spray
- TRG 300 compliant

## Physical and chemical data

- **Basis:** Vaseline
- **Colour:** white
- **Smell:** characteristic
- **Relative density at 20°C:** 0.89 g/ml
- **Yield:** 1.11 g/sec.
- **Vapour pressure at 20°C:** 3 - 4 bar
- **4 Ball EP-test (AS TM D 2596):** 3136 N
- **4 Ball Wear-test (AS TM D 2266):** < 0,4 mm
- **Drop point:** 42°C to 60°C
- **Temperature resistance:** -30°C to +160°C
- **pH-value:** neutral
- **Storage stability:**  
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
aerosol can, maximum nominal volume 400 ml

## Environment and labelling

**Environmentally sound:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling:** All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

## Using instructions

**Before use, carefully read and observe the warning texts on the label!**

### Application:

- Bring spray to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minute before use.
- Spray onto the parts to be treated.
- Optimum lubrication occurs once the solvent has evaporated.

## Tips for spray painting

Protect the object and the surrounding area from spray mist.  
Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

## Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of October 14, 2011  
This release replaces all eventually earlier issued versions.

Print date: 28.04.2024

European Aerosols | Wolfswegweg 2 | 8471 VC Walpers | NL | [info.nl@european-aerosols.com](mailto:info.nl@european-aerosols.com)

