

Technical Information MD 100 Multi-Spray



presto MD 100 Multi-Functional Spray is a high-quality, all-purpose oil for lubricating and protecting metal and rubber parts. Loosens tight screws and removes oil, tar, wax and residues of glue. It is perfect for all types of maintenance at home and in the workshop.

For use on:

Locks, garden tools, gears, pedals, tools, fittings, home trainers

Quality and properties

- Good penetration
- Moisture repellent
- Cleaning effect
- Removes oil, wax, Tectyl and tar
- Good corrosion protection
- Excellent adhesion
- Leaves no residue
- Non-corrosive
- Non-conductive
- Powerful degreaser
- Silicone-free
- Directed jet spray
- TRG 300 compliant

Physical and chemical data

- **Basis:** mineral oil
- **Colour:** brownish
- **Smell:** Vanilla
- **Relative density at 20°C:** 0.80 g/ml
- **Yield:** 1.98 g/sec.
- **Vapour pressure at 20°C:** 3 - 4 bar
- **Temperature resistance:** -50°C to +200°C
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**
aerosol can, maximum nominal volume 400 ml

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EEG in the actually valid version.

Using instructions

Before use, carefully read and observe the warning texts on the label!

Application:

- Bring can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minutes before use.
- Spray a thin coat and flash off. Optimum lubrication occurs once the solvent has evaporated.
- After cleaning, an invisible protective film appears.

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: March 12, 2014

This release replaces all eventually earlier issued versions.

Print date: 03.05.2024

European Aerosols | Wolframweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com