

## Technical Information Ceramic Paste Spray



Metal-free high-temperature paste with excellent lubricating effect. Good corrosion protection. Ideally suited for assembly work on ABS brake systems as well as for long-term lubrication of highly loaded sliding surfaces of all kinds. Temperature resistant from -40 °C to + 1.400 °C. The removable brush head allows for easy even application of the paste.

### For use on:

ABS braking systems, bayonet, plug and screw, pipe, flange joints and fittings

## Quality and properties

- - Metal-free lubrication with extreme temperature resistance
  - Facilitates dismantling, even after long periods of operation
  - Prevents corrosion and squeaks
  - Resistant to chemicals and weathering
  - Resistant to salt water, weak acids and bases
  - Non-conductive

## Physical and chemical data

- **Basis:** grease very fine ceramic particles
- **Colour:** white
- **Smell:** characteristic
- **Relative density at 20°C:** 0.706 g/ml
- **VOC value:** 60%
- **Vapour pressure at 20°C:** 3,5 - 4 bar
- **Temperature resistance:** -40°C to + 1.400°C
- **Storage stability:** 10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:** aerosol can, maximum nominal volume 400 ml

## Environment and labelling

**Environmentally sound:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling:** All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

## Using instructions

**Before use, carefully read and observe the warning texts on the label!**

### Application:

- Shake well before use.
- Remove moisture, dirt and grease from part to be sprayed.
- Spray on the surface without the brush and then spread the paste evenly with the brush head.
- Ensure that grating surfaces are not sprayed!

## Tips for spray painting

Protect the object and the surrounding area from spray mist.  
Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

## Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of July 21, 2016

This release replaces all eventually earlier issued versions.

Print date: 01.05.2024

European Aerosols | Wolfraamweg 2 | 6471 XC Wolvega | NL | [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)