

Technical Information 1K Spray Putty



ColorMatic 1K S spuitplamuur biedt een extreem hoge vulkracht en duurzaamheid. Het is ideaal voor het egaliseren van grote oneffenheden op geschuurde onderlagen en biedt een zeer goede hechting op polyesterplamuur, kunststoffen en metalen.

Toepassing:

Ideaal voor spotrepar en het overspuiten van onderdelen.

Quality and properties

- Very high filling power and durability
- Very good adhesion to polyester filler, plastic and metal
- Simple, time-saving application
- Fast drying time
- Good flow
- Not recoatable with: 1K Füllprimer HG1 und HG7

Physical and chemical data

- **Basis of binder:** Acrylic resin
- **Colour:** beige
- **Smell:** solvent
- **Efficiency:**
400ml are sufficient for approx. 1,25 - 1,75 m²
- **Substrate:**
blank sheet steel, sanded, priming of spare parts, sanded, cured paintings, sanded, polyester substrates, sanded
- **Drying time (at 20°C, 50% relative air humidity):**
Dust dry: 5 min
Dry to touch: 15-20 min
Sandable: 60 min
Hard dry: 60 min
Coatable: 60 min
- **Temperature resistance:** to 110°C
- **Storage stability:**
24 month if appropriate storage provided (=10° - 25°C, relative air humidity of max. 60%)
- **Size:**
Aerosol cans, maximum nominal volume 400 ml
- **VOC-value:** 240,1g

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Using instructions

Before use, carefully read and observe the warning texts on the label!


- Remove all rust from damaged area and sand
- Damaged area must be dry and free of dust and grease
- Shake the can well for 2 minutes
- Carry out spray test
- Attention: after sanding thoroughly clean surface with water-based cleaner. Don't use solvent-based cleaner.
- **For professional use only**
- **Wear an adequate respirator (we recommended type A2/P3)**



2 min




3=70-80µ



5 min




20 min



20°C=60 min
60°C=20 min



P600-800



Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of August 6, 2019

This release replaces all eventually earlier issued versions.

Print date: 01.05.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com