

Technical Information Sanitary Spray



Quick-drying, moisture-resistant spray paint in the most popular sanitary colours! For tone-in-tone design of furnitures and accessories in bathrooms. Suitable for wood, metal, coatable hard plastics, stone, glass, and of course also for basketware and rattan.

For optimal adhesion on the ground choose the suitable primer vom our Basic assortment.

Quality and properties

- High-grade synthetic quality
- Good coverage and filling power
- Good flow, even surfaces
- Fast-drying
- Resistant to moisture
- Colour- and gloss retention

Physical and chemical data

- **Basis of the binder:** Alkyd resin
- **Colour:** diverse
- **Smell:** solvent
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530): glossy: 90-95 gloss units
- **Efficiency:**
Depending on consistence and color of the ground:
400 ml are sufficient for approx. 0.8 - 1.2 m² depending on colour
- **Drying time (at 20°C, 50% relative air humidity):**
Dust-dry: after approx. 30 minutes
Non-sticky: after approx. 3 hours
Cured: after approx. 24 hours
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature-resistant:** up to 80°C
- **Storage stability:**
Aerosols: 10 years, if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:** aerosol cans, maximum nominal volume 400 ml

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Using instructions

The most DUPLI-COLOR spray paints have a so-called no-spray ring or a tamper-proof cap. This is to avoid unauthorized use. Please see the corresponding advises on the cap or on the label.

Before use, carefully read and observe the warning texts on the label!

Application

Preparation of the ground:

- Remove loose flakes of old paints and rust.
- The ground has to be clean, dry and fat-free
- Depending on ground, use DUPLI-COLOR Wood Primer, Metal Primer or Universal Primer.

Lacquering:

- Mask off surfaces not to be painted.
- Before use, shake can for 2-3 minutes.
- Test colour of spray and compatibility at an invisible spot.
- Spray several thin coats in approx. 2 minute intervals.
- Spray distance: approx. 25 cm
- Best results will be achieved during temperatures around 20°C.

Tips for spray painting

Protect the object and the surrounding area from spray mist.
Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: January 7, 2010

This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com