

Technical Information Interiour Dispersion PLUS



DUPLI-COLOR Interiour Dispersion PLUS is absolutely poor in bad odour and pleasant to use. The paintings stand out by high coverage, enormous efficiency and adhesion and high wash resistance.

Possible substrates are: masonry, cement, chalk and synthetic plasters, concrete, gypsum, wallpapers, dispersion paintings.

Quality and properties

- wash resistance
- free from solvents
- ease of use
- high coverage
- breathable
- highly efficient
- very good adhesion

Physical and chemical data

- **Basis of the binder:** acrylat dispersion
- **Colour:** white
- **Smell:** neutral
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530): satin matt
- **Efficiency:** approx. 9 m² per litre
- **Drying time (at 20°C, 65% relative air humidity):** surface dry after approx. 2 hours
re-coatable after approx. 4 hours
The drying time depends on surrounding temperature, air humidity and absorptivity of the ground.
- **Best working temperature and object temperature:** Working and object temperatur should not be below 5°C
- **Cleaning of tools:** immediately after use with water
- **Storage stability:** 2 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%) in the unopened original container.
Do not store below 5°C
- **Size:** 5 litre and 10 litre plastic buckets

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Using instructions

Before use, carefully read and observe the warning texts on the label!

Before coating:

- Cover floors and furniture with a foil.
- Mask off windows and door frames with a masking tape.
- Test the subsoil - it must be firm, dry, clean and stable.
- In case it changes colour to dark during the test with a humid sponge, a primer is necessary.
- Old paintings of glue-bound distemper and chalking surfaces must be completely washed off.
- If necessary, prime with a deep ground.

Coating:

- The colour is ready-to-use and has only to be stirred up carefully.
- It should not be worked if object and working temperatures are below 5°C.
- Can be brushed, rolled or sprayed airless.
- In case of different, contrast-rich and absorbing surfaces it can be a previous coating necessary, diluted with max. 10 % water.
- First paint the corners and edges with a brush or an small roller.
- Then paint the remaining area with a bigger roller.
- In working pauses wrap the brush and roller tightly with a plastic foil.
- After work clean the working tools with water.
- This colour can be recoated after approx. 4 hours.

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of February 8, 2018

This release replaces all eventually earlier issued versions.

Print date: 28.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com