

Technical information Multi-primer



Fast drying multi-primer spray for interior and exterior. Suited as all-purpose primer on iron, steel, zinc, aluminium, anodized aluminium, V2A steel, powder-coated components, different plastics and wood. Active corrosion protection and exceptional adhesion. Heat-resistant to 80°C dry heat and high filling capacity. Adjustable spray cone width (horizontally and vertically).

Application area: On job-sites at renovation. Ideal when fastness and mobility are the primary considerations. For certain preparation of the surface.

Quality and properties

- Universal Primer for steel, galvanized steel, GRP, wood, PVC, etc.
- Excellent preparation of the surface at versatile application possibilities
- Based on synthetic resins
- active corrosion protection
- Weather resistant
- quick drying
- very good adhesion
- heat resistant up to 80°C dry heat
- nitro thinner resistant (after through drying)

Physical and chemical data

- **Basis of binder:** Synthetic resins
- **Colour:** specific
- **Smell:** solvent
- **Efficiency:**
Depending on consistence and colour of the ground:
400 ml are sufficient for approx. 1,5-2 m²
- **Substrate:**
Iron, steel, aluminium, zinc, anodized aluminium, V2A steel, powder-coated components, different plastics like rigid pvc, polyester, polyamide, ABS and wood
- **Drying time (at 20°C, 50% relative air humidity):**
Dust-dry: 40 min
Touch-dry: 60 min
Re-coatable: 3-4 h
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature resistance:** to 80°C (dry heat)
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**
Aerosol cans, maximum nominal volume 400 ml
- **VOC-value:** 740 g

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Using instructions

Before use, carefully read and observe the warning texts on the label!


- Clean surfaces to be painted thoroughly with DUPLI-COLOR Degreaser Spray art.no. 478376, then sand
- The area must be dry and free of dust and grease
- Shake can well for 3 minutes
- Carry out spray test
- 2-3 coats
- Wear an appropriate respirator (type A2/P3)



3 min



20°C=3-4 h



variable



Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of February 16, 2018

This release replaces all eventually earlier issued version.

Print date: 29.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com