

# Technical Information Insulation Tape 5200



PVC insulation tape for universal use. Available in various widths and colours.

### **Quality and properties**

- Suitable for electrical insulation and for a large number of other applications
- Flame retardant
- Maximum temperature: 80°C

### Physical and chemical data

Adhesive: rubberCarrier: PVC

Maximum temperature: 80°C
Tensile strength: 24,5 N/ cm
Adhesive strength: 3 N/ 25 mm

Thickness: 0,15 mm
Breakdown voltage: 6 kV

### **Using instructions**

Temperature: Between 0°C and +30°C

Surface must be clean and free from dust and grease. Stored under appropriate conditions shelf life will be a minimum of 36 months.

# Order information

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of August 14, 2014

This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com