

Technical Information V-Belt Spray



Spray with excellent adhesion to protect V-Belts and to remedy and prevent slipping. The spray is dilatant and user-friendly and gives lasting protection. MoTip V-Belt Spray delays the wear, conditions V-belts and is resistant to weather influences.

For use on:
V belts

Quality and properties

- User-friendly
- Remedies and prevents slipping and creaking
- Excellent adhesion
- Lasting protection
- Dilatant
- Resistant to weather influences
- Conditions V-Belts
- Delays the wear of V-Belts
- Directed jetspray

Physical and chemical data

- **Basis:** Polyalphaolefine
- **VOC-content:** approximately 92% w/w
- **Colour:** transparent
- **Smell:** characteristic
- **Relative density at 20°C:** 0.89 g/ml
- **Yield:** 1.15 g/sec.
- **Vapour pressure at 20°C:** 3 - 4 bar
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**
aerosol can, maximum nominal volume 500 ml

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EEG in the actually valid version.

Instruction manual

Before use, carefully read and observe the warning texts on the label!

Application:

- Bring can to room temperature.
- Operating temperature 5 to 30°C.
- Switch off engine.
- Shake can for 2 minutes before use.
- Apply a thin, even coat of V belt spray on the running surface of the V belt and leave to work. Once the solvent has evaporated, the engine can be restarted.

Tips for spray painting

Protect the object and the surrounding area from spray mist.
Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: October, 1 2014

This release replaces all eventually earlier issued versions.

Print date: 28.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com