

Technical Information Gasket Remover

Spray for the fast and easy removal of dried adhesives and seals, as well as hardened sealing material from car and machine parts. Gasket remover has high dissolving properties and is non-conductive and non-corrosive. In view of the high viscosity, gasket remover has optimum effect. MoTip Gasket Remover is user-friendly and has a directed jetspray.

For use on:

Metal, wood, ceramic, glass, polyethylenes and polypropylenes

Quality and properties

- User-friendly
- High dissolving properties
- Optimum effect in view of high viscosity
- Non-conductive
- Slight gel structure
- Non-corrosive
- Directed jetspray
- Electro engines

Physical and chemical data

- **Basis:** Dimethoxymethan
- **VOC-content:** approximately 95% w/w
- **Colour:** transparent
- **Smell:** Ether
- **Relative density at 20°C:** 0,75 g/ml
- **Yield:** 1,0 - 1,5 g/sec.
- **Vapour pressure at 20°C:** 2 - 3 bar
- **pH-value:** neutral
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**
aerosol can, maximum nominal volume 500 ml

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Instruction manual

Before use, carefully read and observe the warning texts on the label!

Application:

- Bring can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minutes before use.
- Cover coated or plastic parts.
- Spray the residue to be removed from a distance of ca. 25-30 cm and leave to work for 10 minutes.
- Carefully remove loosened residue with a spatula.
- Repeat process on stubborn dirt.

Tips for spray painting

Protect the object and the surrounding area from spray mist.
Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: November 2, 2011

This release replaces all eventually earlier issued versions.

Print date: 30.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com