

Technical Information Silicone Spray



This is a high-quality silicone spray for lubricating and protecting plastic and rubber parts against moisture, dirt and rust on bikes. It impregnates rubber and prevents plastic parts from breaking and squeaking.

Quality and properties

- o Prevents plastic parts from squeaking and creaking
- o Excellent adhesion
- o Water repellent
- o Excellent mechanical and thermo stability
- o Long-lasting shine
- o Weatherproof
- o Weak acid and basis proof
- o PH neutral

Physical and chemical data

- **Temperature resistance:** -50°C to +200°C
- **Disruptive strength:** 14 kv/mm at a temperature of 20°C
- **Size:**
aerosol can, maximum nominal volume 200 ml

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Instruction manuel

Before use, carefully read and observe the warning texts on the label!

Application:

- Bring can to room temperature.
- Operating temperature 15 to 25°C.
- Shake can for 2 minutes before use.
- Apply silicone spray in a thin layer.
- Best lubrication once the solvent has evaporated (ca. 1 minute).
- Apply a thin even coat and spread with a soft cloth for a brilliant shine.
- Leave to work for a minute and then polish.

Order informations

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: May 7, 2010

This release replaces all eventually earlier issued versions.

Print date: 28.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com