

## Technical Information Cycling Super Lubricant



High quality, low viscous lubricant to treat all non bearing, moving parts of bicycles, with the exception of chains. Extremely suitable to treat part of carbon, aluminium, steel and plastic, both treated and untreated.

Applications: derailleur, gear cable, brake cable, gear levers and shifters, brake levers and lock

### Quality and properties

- Low friction factor for minimal resistance
- Excellent lubricating properties
- Contains PTFE
- Prevents wear
- Reduces the adhesion of dirt
- Resistant to weather influences
- Water-repellent
- Directed Jetspray
- Sprayable at any angle due to a 360° valve.

### Physical and chemical data

- **Basis of the binder:** synthetic oil with PTFE
- **Colour:** transparent
- **Smell:** characteristic
- **Relative density at 20°C:** 0,91 g/ml
- **Yield:** 1,5 – 2,0 g/sec
- **Vapour pressure at 20°C:** approx. 3 bar
- **Storage stability:**  
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
aerosol cans, maximum nominal volume 400 ml

### Environment and labelling

**Environmentally sound:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling:** All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

### Instruction manuel

**Before use, carefully read and observe the warning texts on the label!**

#### Application:

- The aerosol should have room temperature.
- Best processing temperature 5 to 30°C.
- Shake for 2 minutes before use.
- The surface should be clean and dry.
- Apply super lubricant in a thin layer.

### Tips for spray painting

Protect the object and the surrounding area from spray mist.  
Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: October 24, 2011  
This release replaces all eventually earlier issued versions.

Print date: 27.04.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)