

## Technical Information Carburettor Cleaner



Cleaner for the interior and the exterior of carburettors and valves, without disassembly. Carburettor cleaner has high dissolving properties and leaves no residue. MoTip Carburettor Cleaner is non corrosive and has a directed jetspray.

### Quality and properties

- Directed jetspray
- High dissolving properties
- Leaves no residue
- Non-corrosive
- 360° valve

### Physical and chemical data

- **Basis:** Hydrocarbons
- **VOC-content:** 100% w/w
- **Colour:** transparent
- **Smell:** characteristic
- **Relative density at 20°C:** 0.84 g/ml
- **Yield:** 3,00 g/sec.
- **Vapour pressure at 20°C:** 3 - 4 bar
- **Storage stability:**  
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
aerosol can, maximum nominal volume 500 ml

### Environment and labelling

**Environmentally sound:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling:** All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

### Instruction manual

**Before use, carefully read and observe the warning texts on the label!**

#### Application:

- Bring can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can before use.
- Switch off the engine and allow to cool down. Remove the air filter.
- Spray the exterior of the carburettor until the contamination has disappeared.
- Spray the visible part of the interior of the carburettor and allow to take effect.
- Start the engine and let idl with very limited speed. Spray carburettor cleaner several times at the air inlet and increase the speed of the engine. Switch the engine off and install the air filter.

### Tips for spray painting

Protect the object and the surrounding area from spray mist.  
Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: October 01, 2014

This release replaces all eventually earlier issued versions.

Print date: 06.05.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wol Vega | NL | [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)