

Technical Information Quick Start



Effective tool for starting problems with internal combustion engines. Inject the ether-based MoTip Quick Start into the air inlet of the air filter for several seconds and start the engine.

For use on:

Combustion engines of all kinds e.g. car, bicycles, lorries, vans, chain saws, trimmers, tractors

Quality and properties

- Fast-acting
- Ether-based
- Misty spray pattern

Physical and chemical data

- **Basis:** Diethylether and mineral oil
- **VOC-content:** approximately 99,5% w/w
- **Colour:** transparent
- **Smell:** characteristic
- **Relative density at 20°C:** 0.711 g/ml
- **Yield:** 1.70 g/sec.
- **Vapour pressure at 20°C:** 3 - 4 bar
- **Flash point:** -40°C
- **Explosion limit:** Lowest 1.7 Vol%, Highest 36 Vol%
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**
aerosol can, maximum nominal volume 500 ml

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Instruction manuel

Before use, carefully read and observe the warning texts on the label!

Application:

- Bring the can to room temperature.
- Shake can for 2 minutes before use.
- Spray MoTip quick start spray for a few seconds in the air filter inlet.
- Then, start the engine immediately.
- For petrol engines – keep foot on the accelerator during ignition.
- For diesel engines – start the engine and leave running.
- In very cold conditions, continue to spray for a few seconds after ignition.
- **Do not use with preheat spirals or candles or other preheat devices.**

Tips for spray painting

Protect the object and the surrounding area from spray mist.
Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: November 2, 2011
This release replaces all eventually earlier issued versions.

Print date: 06.05.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com