

Technical Information Battery Pole Protection Spray



presto Battery Pole Protection Spray protects electrical contacts and battery terminals from oxidation and corrosion. The blue wax ensures a constant flow of electricity and prevents leakage and voltage losses. It extends the life of a battery and prevents acid damage. Good compatibility with plastics.

Applications: battery terminals, battery holders, terminals, earth cables

Quality and properties

- Long-term prevention from corrosion and oxidation
- Safe ignition and bright lighting
- Prevents acid damage
- Insulating effect
- Prevents leakage and contact resistance
- Extends the life of a battery
- Directed jet spray
- Can be sprayed from any angle due to a special 360 ° valve.
- Observe TRG 300

Physical and chemical data

- **Basis:** Wax
- **Colour:** blue
- **Smell:** waxy
- **Appearance:** fat
- **Relative density at 20°C:** 0.695 g/ml
- **Vapour pressure at 20°C:** 3 - 4 bar
- **Temperature resistant:** -30°C to +130°C
- **pH-value:** neutral
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**
aerosol can, maximum nominal volume 400 ml

Environment and labelling

Environmentally sound: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EEG in the actually valid version.

Using instructions

Before use, carefully read and observe the warning texts on the label!

Application:

- Make sure can is at room temperature.
- Application temperature 5-30°C.
- Parts to be protected must be clean and dry.
- Shake can well before use.
- Spray a thin layer of battery terminal protection on the parts to be treated.

Order informations

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of March 12, 2014

This release replaces all eventually earlier issued versions.

Print date: 04.05.2024

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com