

Technical Information Silicone Remover



ColorMatic siliconenverwijderaar is essentieel voor professionele lakresultaten, omdat het vuil, vet, olie, siliconen, was, teer, lijmresten etc. grondig verwijdt. Het gebruik van ColorMatic siliconenverwijderaar bespaart veel tijd, is snel en gemakkelijk te gebruiken en is universeel toepasbaar. Het verbetert de hechting voor de daaropvolgende coatings.

Toepassing:

Ideaal voor spotrepair, het overspuiten van onderdelen en voor alle werkzaamheden die een professionele reiniging vereisen.

Quality and properties Physical and chemical data

- Simple, time-saving application
- Thorough removal of silicone, grease, oil, wax, dirt, tar, adhesive residues etc.
- Mild, non-aggressive solvent
- Improves adhesion of subsequent coatings
- Extremely time saving
- Desalination function

- **Colour:** transparent
- **Smell:** solvent
- **Efficiency:** very good
- **Substrate:** primed and filled areas
metal, glass
old paints and original paints from supplier
painted and unpainted surfaces
- **Storage:** 10 years if appropriate storage provided (=10° - 25°C, relative air humidity of max. 60%)
- **Size:** Aerosol cans, maximum nominal volume 400 ml
- **VOC-value:** 269,7g

Disposal and labelling

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.


Using instructions

Before use, carefully read and observe the warning texts on the label!

Instructions:

- Shake the can shortly before use
- 1 - 2 light coats, repeat if dirt excessive
- Wipe off with a clean, dry, non-woven cloth
- Allow cleaned surfaces to dry
- Suitable for all levelled, primed and filled surfaces
- Suitable for metal and glass
- Suitable for old and original paintwork

- Suitable for painted and unpainted undercoats
- **For professional use only**
- **Wear an appropriate respirator (we recommend A2/P3)**



Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of August 6, 2019

This release replaces all eventually earlier issued versions

Print date: 16.08.2026

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com