

Technical information Guide Coat Black



ColorMatic schuurgids zwart is een hoogwaardige acrylverf die snel droogt en wordt gebruikt voor het opsporen van poriën, scheuren, oneffenheden en schuursporen na het aanbrengen van plamuur of vulmiddel. De zeer fijne verneveling garandeert een gelijkmatige applicatie en betrouwbare resultaten.

Toepassing:

De ideale hulp voor perfect schuren na het aanbrengen van plamuur en vulmiddel.

Quality and properties Physical and chemical data

- High-quality acrylic coat
- Fast drying time
- Useful for identifying pores, cracks and sanding marks
- Very fine atomisation ensures reliable results

- **Basis of binder:** Acrylic
- **Colour:** black
- **Smell:** solvent
- **Substrate:**
very good dried and polished putties, primer or filler areas
- **Temperature resistance:** to 80°C
- **Storage stability:**
10 years if appropriate storage provided
(=10°-25°C, relative air humidity of max. 60%)
- **Size:**
Aerosol cans, maximum nominal volume 400 ml
- **VOC-value:** 257,5g

Disposal and labelling

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Using instructions

Before use, carefully read and observe the warning texts on the label!


- No special preparation required before applying ColorMatic guide coat black
- Shake the can well for 2 minutes
- Carry out spray test
- When using dark fillers/ primer fillers, we recommend using ColorMatic primer filler HG1, No. 856 532, know as guide coat white
- **For professional use only**
- **Wear an appropriate respirator (recommended type A2/P3)**



2 min



1



grindable 2-3
min

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of July 26, 2010

This release replaces all eventually earlier issued versions.

Print date: 15.08.2026

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com