

Technical Information Sheet Wheel Spray Silver Chrome



ColorMatic velgenlak zilverchroom is een spray met hoogglanseffect, die gladde oppervlakken eruit laat zien als chroom. Het is weer- en slijtvast.

Voor een optimale hechting, voor het aanbrengen aluminium wielen primen met [ColorMatic 1K Primer voor aluminium \(Art. no. 190278\)](#). Stalen wielen voorstrijken met [ColorMatic 1K Primer Filler](#). **Belangrijk:** voor een perfect resultaat is een zeer gladde, glanzende zwarte grondlaag vereist, (bijvoorbeeld door [ColorMatic RAL diep zwart glans acrylaatspuitverf Art. no. 856631](#) aan te brengen).

Toepassing:

Ideaal voor het coaten van nieuwe of gebruikte autovelgen, effect afhankelijk van een gladde, glanzende zwarte grondlaag.

Quality and properties Physical and chemical data

- High-gloss spray effect: the smooth surface makes it look like chrome
- Simple, time-saving application
- Fast drying time
- Exceptionally high coverage
- Resistant to rocks, salt etc.
- Abrasion resistant
- Robust against damage during automatic car wash

- **Basis of binder:** Acrylic
- **Colour:** chrome silver
- **Smell:** solvent
- **Efficiency:**
Depending on consistence and colour of the ground:
400 ml are sufficient for approx. to 1,5m² or 4 wheels
- **Substrate:**
Thoroughly cleaned, new or second-hand steel or aluminium wheel rim
- **Drying time (at 20°C, 50% relative air humidity):**
Dust-dry: after approx. 10 minutes
Dry to touch: after approx. 30 minutes
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature resistance:** to 150°C
- **Storage stability:**
10 years if appropriate storage provided
(=10°-25°C, relative air humidity of max. 60%)
- **Size:**
Aerosol cans, maximum nominal volume 400 ml
- **VOC-value:** 304,1g

Disposal and labelling

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EEC in the actually valid version.

Using instructions

Before use, carefully read and observe the warning texts on the label!


- Clean surfaces to be painted thoroughly with [ColorMatic silicone cleaner no. 174469](#), then sand
- The area must be dry and free of dust and grease
- Shake can vigorously for 2 minutes
- Carry out spray test
- For optimum adhesion before application, prime the aluminium wheels with [ColorMatic 1K primer for aluminium no. 180278](#). Prime steel wheels with [ColorMatic 1K primer filler](#)
- Several thin coats (5-6 paint) on a black background with drying period between of 2-3 minutes
- **Important:** to achieve an optimal effect, a very smooth, shiny black surface is required (e.g. by applying ColorMatic RAL glossy jet black acrylic spray paint no. 856631)
- **For professional use only**
- **Wear an appropriate respirator (recommended type A2/P3)**




2 min




3-4



5 min



20°C=60 min



Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of July 26, 2010

This release replaces all eventually earlier issued versions

Print date: 16.08.2026

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com