

Technical Information Sheet Paint Repair Set



With the ColorMatic Paint Repair Set for stone-chipps laymen can refinish small damages on the original car paint work fast and effective. The set includes, excepting the paint stick in fitted colour, all necessary components. Just in a few steps punctual as well as extensive small, irritating damages can be eliminated.

Applications:
For stone-chippings for the DIY application.

Quality and properties Physical and chemical data

- Quick and simple use
 - Just in a few steps to obvious less stone-chippings
 - Cost-saving
 - The set includes all necessary parts, excepting the fitting paint stick
 - Useable for all original car paints
 - Useable punctual as well as extensive
 - Application film on CD
 - Content:
 - Reparation fluid 50 ml
 - Rubber squeegee
 - Polish tissue
 - One way gloves
 - Step by step application guide
 - CD wit application film
 - Don't use on hot areas!
 - Don't use in the blazing sun!
- **Color:** transparent
 - **Smell:** solvent
 - **Substrate:** clean, dry, fat- and rust-free
 - **Temperature resistance:** to 80°C
 - **Storage stability:**
 - 5 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
 - **Size:**
 - Reparation fluid 50 ml

Disposal and labelling

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Using instructions

Before use, carefully read and observe the warning texts on the label!

Anwendung

- Clean thoroughly with water the area which is to paint
- Possibly clean with [ColorMatic Silikonreiniger, Art.Nr. 174469](#)
- The area have to be dry, fat-, dust- and rust-free
- Give a few drops of the fitting paint from the paint stick (not included) at the rubber squeegee
- Move the squeegee about the damaged area
- Dry approx. 5 minutes
- Wrap the squeegee with the tissue tautly and single-layer
- Moisten the polish tissue with the reparation fluid

- Rub against the paint coat with the moistened tissue, except of the paint into the stone-chips or scratches, the paint should be removed
- Clean again with water and a microfibre tissue
- Possibly polish

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of March 19, 2014

This release replaces all eventually earlier issued versions

Print date: 16.08.2026

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com