

Technical Information Forestry Marking Spray Neon



Distein Forestry Marking Spray is to be used for marking of trees, wood and stone also.

Distein Forestry Marking Spray with its reliable adhesion on wet surfaces is weather- and water-proof.

Quality and properties Physical and chemical data

- Awarded with the „KWF-Test“ approval mark
 - Weather-proof, good adhesion on wet surfaces and direct insolation
 - Ideal opacity and fluorescence
 - Frost-proof till -20° C
 - Minimal drizzle
 - The special nozzle is perfect for flat spraying and wood marking
 - High yield
 - Easy colour-recognition with patented coloured donut
 - Application is possible with metal spray handle
- **Colours:**
Neon-red, Neon-orange, Neon-yellow, Neon-blue, Neon-green, Neon-pink, black, white
 - **Efficiency:**
Depending on surface and colour 500 ml are sufficient for approx. 3-4 m²
 - **Drying:**
Dust-dry: after 10 minutes
Dry to touch: after 30 minutes
Fully dried: after 24 hours
 - **Disposal:**
Only the completely empty can should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".
 - **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
 - **Container:**
Maximum nominal volume = 500 ml

Disposal and labelling

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Using Instructions

Before use, carefully read and observe the warning texts on the label!

- Before use, shake can well for 2 minutes.
- Spray to test colour and compatibility on an inconspicuous area.
- Distance approx 10-15 cm
- After use, turn the can upside down and briefly clear the valve to prevent nozzle clogging

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of April 30, 2026

This release replaces all eventually earlier issued versions.

Print date: 15.08.2026

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com