



Technical Information Fly Enamel Spray



Enamel Spray for quick and easy repair of irritating scratches or similar small damages on white enamel surfaces such as bath-tubs, sinks, toilet bowls, instantaneous water-heaters, refrigerators etc.

Not suitable for **large-area** repairs at wash-bowls, bathtubs etc.

Quality and properties Physical and chemical data

- High-grade acrylic quality
- For white glossy enamel surfaces
- Hard, durable surface
- Very good coverage
- Excellent adhesion
- Good flow, smooth surface
- Quick-drying
- Scratch-, shock- and impact-resistant

- **Basis of the binder:** Acrylic copolymers
- **Colour:** enamel-white
- **Smell:** solvent
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530):
glossy: 80-85 gloss units
- **Efficiency:**
400 ml are sufficient for approx. 0.8 - 1.5 m²
- **Drying time (at 20°C, 50% relative air humidity):**
Dust-dry: after approx. 5 minutes
Cured: after approx. 2 hours
Resilient: after approx. 48 hours
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature-resistant:** up to 80°C
- **Storage stability:**
Aerosols: 10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:** aerosol cans with maximum nominal volume 400 ml

Disposal and labelling

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Using instructions

The most DUPLI-COLOR spray paints have a so-called no-spray ring or a tamper-proof cap. This is to avoid unauthorized use. Please see the corresponding advises on the cap or on the label.

Before use, carefully read and observe the warning texts on the label!

Applicaton

Preparation of the ground:

- Remove loose parts, rust and dirt.
- The surface has to be clean, dry and free of fat.
- Slightly sand the damaged area and a small part of the surrounding surface.
- Remove abrasive dust.

Lacquering:

- The aerosol can should have room temperature.
- Before use shake the can vigorously for 2-3 minutes.
- Test colour of spray and compatibility of the lacquer at an invisible spot.
- Spray several thin cross-coats from a distance of approx. 25 cm.
- Do not spray over synthetic paints!

Tips for spray painting

Protect the object and the surrounding area from spray mist.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Order informations

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of June 15, 2016

This release replaces all eventually earlier issued version

Print date: 25.08.2026

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com