

Technical information Quick Check spray



ColorMatic Quick Check spray voor het controleren van geschuurde oppervlakken om onregelmatigheden op te sporen. Geeft een tijdelijke glans die residuvrij verdampt. Ook te gebruiken voor het controleren van de kleur van spuitmonsters.

Toepassing:

Het ideale hulpmiddel voor perfect schuren na het aanbrengen van een blanke laklaag.

Quality and properties Physical and chemical data

- Sprays gloss in a matter of seconds
- Evaporates residue-free
- Useful for identifying smallest dents and irregularities
- Produces colorfast spray samples
- Easy to use
- Ensures perfect results

- **Basis of binder:** Aliphatic hydrocarbons
- **Colour:** transparent
- **Smell:** solvent
- **Substrate:**
sanded primer or filler areas
- **Storage stability:**
10 years if appropriate storage provided
(=10°-25°C, relative air humidity of max. 60%)
- **Size:**
Aerosol cans, maximum nominal volume 400 ml
- **VOC-value:** 276,0g

Disposal and labelling

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EEC in the actually valid version.

Using instructions

Before use, carefully read and observe the warning texts on the label!

Application


- No special preparation required before applying ColorMatic Quick Check spray
- Shake the can for 5 seconds
- Surface check: Apply ColorMatic Quick Check in 1-2 thin layers. Rub with a paper tissue until an even surface film is arising
- Color check: Apply ColorMatic Quick Check on the basecoat lacquered spray sample and also on the car part which is for comparison
- After 20 minutes (depends on ambient temperature) the film is residue-free evaporated
- Tolerability testing is needed
- **For professional use only**
- **Wear an appropriate respirator (recommended type A2/P3)**



5 sec



1-2



Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of November 7, 2018

This release replaces all eventually earlier issued versions.

Print date: 16.08.2026

European Aerosols | Wolfraamweg 2 | 8471 XC Wolvega | NL | info-nl@european-aerosols.com